



PRICE LIST

Ref No. RRKL/LP/BCISI/11-1/24
w.e.f. 19th November 2024

THE ONLY INDIAN
WIRE BRAND
TRUSTED BY

90+

COUNTRIES
GLOBALLY



RR KÄBEL
WIRES & CABLES

**AKALMAND BANO,
SAHI CHUNO.**

AKALMAND BANO, SAHI CHUNO.



BUILDING WIRES

RR KÄBEL
WIRES & CABLES

INDIA'S ONLY WIRE WITH
REACH • RoHS
CE • CPR Compliant



SUPEREX FR FR PVC Insulated Single Core Cables



RR Kabel makes Single Core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
0.75	24/0.2	1417	24
1.0	14/0.3	1931	24
1.5	22/0.3	2815	16
2.5	36/0.3	4505	12
4.0	56/0.3	6565	8
6.0	84/0.3	9781	4

UNILAY HR FR HR FR PVC Insulated Single Core Cables



RR Kabel makes Single Core unsheathed Multistrand flexible High Conductivity plain annealed copper, HR FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.0	37/0.19	2023	24
1.5	37/0.23	2941	16
2.5	61/0.23	4715	12
4.0	61/0.29	7202	8
6.0	91/0.29	10706	4

FIREX LSOH HALOGEN FREE FLAME RETARDANT 90°C, CROSSLINKED



RR Kabel makes Single Core unsheathed Multistrand High Conductivity plain annealed Copper, Cross linked Halogen Free Flame Retardant (HFFR) 90° C Insulated Industrial Cables in voltage grade upto and including 1100 volts, as per IS 17048 (HSN Code: 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.00	14/0.3	2378	24
1.50	22/0.3	3350	16
2.50	36/0.3	5307	12
4.00	56/0.3	7788	8
6.00	84/0.3	11281	4

* FIREX LSOH - Insulation Conforming to HFI XL 90 as per IS 17048

RR KABEL FR HSF / FR-LSH



RR KABEL

RR Kabel makes Single Core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC/FR-LSH PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, As per IS 694 (HSN Code: 8544)

RATE / 200 MTR					
Size (Sq.mm)	Configuration	AMPS	RR KABEL FR HSF FR PVC INSULATION	RR KABEL FR-LSH FR-LSH PVC INSULATION	No. of Coils packed in an Outer Box
0.75	24/0.2	8	3407	3523	12
1.0	32/0.2	13	4448	4604	12
1.5	30/0.25	17	6432	6652	8
2.5	50/0.25	24	10472	10840	6
4.0	56/0.3	30	16098	16664	4
6.0	84/0.3	38	23941	24718	2

LSOH-FR



RR KABEL

RR Kabel makes Multistrand High Conductivity Plain Copper Thermoplastic Halogen Free Flame Retardent (HFFR) 70° C Insulated Single Core Unsheathed Industrial Cables in Voltage Grade Upto and Including 1100 Volts, As Per IS 17048 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	AMPS	Unit	Rate	No. of Coils packed in an Outer Box
0.75	24/0.2	8	180 Mtr	3430	12
1.0	32/0.2	13	180 Mtr	4322	12
1.5	30/0.25	17	180 Mtr	6080	8
2.5	50/0.25	24	180 Mtr	9840	6
4.0	56/0.25	30	180 Mtr	15088	4
6.0	84/0.3	38	180 Mtr	22372	2

FR HSF



RR KABEL

RR Kabel makes Multistrand High Conductivity Plain Copper FR PVC Insulated Single Core Unsheathed Industrial Cables in Voltage Grade Upto and Including 1100 Volts, As Per IS 694 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	AMPS	Unit	Rate	No. of Coils packed in an Outer Box
0.75	24/0.2	8	180 Mtr	2870	12
1.0	32/0.2	13	180 Mtr	3751	12
1.5	30/0.25	17	180 Mtr	5423	8
2.5	50/0.25	24	180 Mtr	8850	6
4.0	56/0.25	30	180 Mtr	13542	4
6.0	84/0.3	38	180 Mtr	20134	2



COMMUNICATION CABLES

RR KĀBEL
WIRES & CABLES

- RATNA CO-X
- RATNA LAN
- RATNA COM
- CCTV CAMERA CABLE
- SPEAKER CABLE

RATNA CO-X



RR Kabel makes Electrolytic grade solid annealed bare copper conductor gas injected physical polyethylene foam insulated, wrapped with Aluminium Mylar tape and Al alloy wire braided, Jelly flooded and PVC Jacketing in Black Colour, Co-Axial Industrial Cables. (HSN Code : 8544)

RG 59 F		RG 6 F		RG 11 F	
90 Mtr.	305 Mtr.	90 Mtr.	305 Mtr.	90 Mtr.	305 Mtr.
2152	7298	2753	9326	6132	20783

RATNA LAN



RR Kabel makes Solid bare copper conductor 4 Pair unshielded twisted pair (UTP) Industrial cables for Computer Lan Network with Grey colour & FR PVC Jacket. (HSN Code : 8544)

CAT 5e		CAT 6	
100 Mtr.	305 Mtr.	100 Mtr.	305 Mtr.
3437	10475	4591	14006

RATNA COM



RR Kabel makes Solid Electrolytic annealed bare copper conductor Industrial Switchboard & Telephone Cables with high density polyethylene insulation, paired, polyester taped, Nylon Rip Cord and Grey colour sheathed with FR PVC, generally conform to "ITD specification S/WS 113 C" (HSN Code : 8544) (Rate/90 Mtr Coil)

Dia	1 Pair	2 Pair	3 Pair	4 Pair	5 Pair	10 Pair	20 Pair
0.5 mm	997	1755	2585	3389	4223	8068	15315

CCTV CAMERA CABLES



RR Kabel makes Annealed Tinned copper conductor, PE Insulated, ATC Braided, Polyester tape screened, PVC outer sheathed Industrial CCTV Camera Cables.(HSN CODE : 8544)

Size	Packing	Rate Per Coil	No. of Coils packed in an Outer Box
3 + 1	90 Mtr.	4097	3
4 + 1	90 Mtr.	4591	3

SPEAKER CABLES



RR Kabel makes Multistrand Annealed bare copper conductor, PVC Insulated Industrial Speaker wires. (HSN CODE : 8544)

Size	Packing	Non Transparent Insulation (Rate/Coil)	Transparent Insulation (Rate/Coil)	No. of Coils packed in an Outer Box
2C x 0.50	90 Mtr.	1997	2057	10
2C x 0.75	90 Mtr.	2847	2932	10
2C x 1.0	90 Mtr.	3587	3695	8
2C x 1.5	90 Mtr.	5176	5331	8
2C x 2.5	90 Mtr.	8244	8491	8



INDUSTRIAL CABLES

RR KÄBEL
WIRES & CABLES

- FLEXIBLE SINGLE CORE CABLE
- FLEXIBLE MULTICORE CABLES
- SHIELDED CABLE
- BRAIDED CABLE

RR KABEL FR HSF / FR-LSH / LSOH-FR



RR Kabel makes single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC/FR-LSH PVC/ Thermoplastic Halogen free Flame Retardant (HFFR) 70° Insulated Industrial Cables in voltage grade upto and including 1100 Volts (HSN Code : 8544)

RATE / 100 MTR					
Size (Sq.mm)	Configuration	AMPS	RR KABEL FR HSF FR PVC INSULATION As Per IS 694	RR KABEL FR-LSH FR-LSH PVC INSULATION As Per IS 694	RR KABEL LSOH-FR <small>Thermoplastic Halogen Free Flame Retardant (HFFR) 70° C Insulation As Per IS 17048</small>
10.0	140/0.3	52	21019	21751	23092
16.0	126/0.4	70	33270	34430	36368
25.0	196/0.4	88	53730	55880	60181
35.0	276/0.4	112	75161	78167	84178
50.0	396/0.4	146	107187	111472	120047
70.0	360/0.5	216	151901	157977	170127
95.0	480/0.5	262	204341	212515	228862
120.0	608/0.5	310	264401	274981	296132
150.0	750/0.5	355	327760	340874	367090
185.0	931/0.5	415	398619	414565	446451
240.0	1200/0.5	500	524417	545393	587347
300.0	1500/0.5	550	654683	680873	733245
400.0 *	2013/0.5	590	889625	925212	996380
500.0 *	2562/0.5	660	1153166	1199290	1291544
630.0 *	3416/0.5	725	1532893	1594208	1716840

The item marked * are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.

** RR Kabel LSOH-FR: Insulation conforming to HFI TP 70 as per IS 17048

RR KABEL FR HSF SINGLE CORE



Multistrand bright electrolytic annealed bare copper conductor, FR PVC Insulated Unsheathed Single core round flexible Industrial Power Cables for working voltages upto and including 1100 Volts as per IS 694 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	AMPS	Rate Per 100 Mtr
0.5	16/0.2	5	1205
0.75	24/0.2	8	1694
1.0	32/0.2	13	2207
1.5	30/0.25	17	3192
2.5	50/0.25	24	5200
4.0	56/0.3	30	7949
6.0	84/0.3	38	11826


RATNA FLEX MULTICORE CABLES



RR Kabel makes Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated & PVC sheathed multicore round flexible Industrial Cables for working voltages upto and including 1100 Volts, as per IS 694 (HSN CODE : 8544)

Rate per 100 meter											
Size (Sq.mm)	CONFIG.	AMPS	2 CORE	3 CORE	4 CORE	Size (Sq.mm)	CONFIG.	AMPS	2 CORE	3 CORE	4 CORE
0.5	16/0.2	5	3446	4547	5717	25.0	196/0.4	88	121734	172577	227370
0.75	24/0.2	8	4538	6112	7810	35.0	276/0.4	112	-	240999	319359
1.0	32/0.2	13	5560	7765	9942	50.0	396/0.4	146	-	344023	448015
1.5	30/0.25	17	7683	10619	13825	70.0	360/0.5	216	-	484013	638074
2.5	50/0.25	24	12163	17035	22156	95.0	480/0.5	262	-	652923	856122
4.0	56/0.3	30	18686	26209	34337	120.0	608/0.5	310	-	824285	1091677
6.0	84/0.3	38	26938	38424	50558	150.0	750/0.5	355	-	1046314	1372344
10.0	140/0.3	52	47367	67870	88442	185.0	931/0.5	415	-	1285698	1669572
16.0	126/0.4	70	74002	104513	137712	240.0	1200/0.5	500	-	1670945	2257961
						300.0	1500/0.5	550	-	2084318	2820401

CONTROL CABLES



RR Kabel makes Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated & PVC sheathed multicore round flexible Industrial Control Cables (JZ-500), Voltages Grade 300/500 V. (HSN CODE : 8544)

Rate per 100 meter												
Size (Sq.mm)	CONFIG.	AMPS	5 CORE *	6 CORE *	7 CORE *	8 CORE *	10 CORE *	12 CORE *	14 CORE *	16 CORE *	19 CORE *	24 CORE *
0.5	16/0.2	5	7707	8994	10025	11901	14763	17341	20088	22533	26586	34035
0.75	24/0.2	8	10515	12647	14174	16998	20782	24719	28709	32747	39486	49456
1.0	32/0.2	13	13427	15738	17921	21347	26604	31264	36621	41060	50623	62303
1.5	30/0.25	17	18779	22294	25506	29912	37451	44205	51468	57970	68590	87882
2.5	50/0.25	24	29930	36289	41578	48216	60750	71542	83921	95927	114089	143219
4.0	56/0.3	30	46484	56590	65381	76997	96233	113996	132766	151315	178756	228387
6.0	84/0.3	38	69269	83826	97693	113017	144411	171177	198420	225998	266684	340267
10.0	140/0.3	52	118351	-	-	-	-	-	-	-	-	-
16.0	126/0.4	70	186493	-	-	-	-	-	-	-	-	-

Loading factor for Different Insulation / Sheath * -

FR Insulation	FR Sheath	FR-LSH / HR Insulation	FR-LSH / HR Sheath	LSOH Insulation	LSZH Sheath
5%	5%	10%	10%	35%	25%

The item marked * are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.

SUBMERSIBLE FLAT CABLES

RR Kabel makes 3 Core PVC Insulated and sheathed Industrial Flat cables for Submersible Motor, working voltages upto and including 1100 Volts, as per IS 694



Size (Sq.mm)	Configuration	Rate 100 mtr
1.5	22/0.3	11349
2.5	36/0.3	17696
4.0	56/0.3	25943
6.0	84/0.3	37621
10.0	140/0.3	65505
16.0	126/0.4	101590
25.0	196/0.4	159564

* For XLPE Insulated Submersible Flat Cables (Cu/XLPE/PVC), contact us for pricing and availability. MOQ will be applicable.

ONLY THE BEST SUBMERSIBLE CABLES CAN WITHSTAND THE HARSHTEST CONDITIONS.

- PVC & XLPE Insulation
- Electrolytic Grade Annealed Copper
- Better Conductivity
- CE, REACH & RoHS Compliant



AKALMAND BANO, SAHI CHUNO.

SHIELDED CABLES



RR Kabel makes Flexible / Stranded Bare Copper Conductor, PVC Insulated, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Shielded) Cables, Voltage Grade 300/500V, as per BS EN 50288-7

SIZE	Size in Sq.mm / Rate Per 100 Meter (in INR)					MOQ (KM)
	0.50	0.75	1.00	1.50	2.50	
2 Core	6329	7676	8941	11436	16818	3
3 Core	7922	9930	11801	15230	23377	3
4 Core	9908	12574	15099	19930	30149	3
5 Core	11385	14765	17933	24024	37443	3
6 Core	13304	17339	21342	27998	-	3
7 Core	14759	19472	23841	31871	49059	3
8 Core	16729	22170	26991	36515	58234	2
9 Core	18496	-	-	-	-	2
10 Core	20509	27271	33594	46087	72220	2
12 Core	23760	31886	39833	53838	85622	2
14 Core	27054	36178	45845	62230	100349	1
16 Core	30683	42023	51813	70547	114530	1
18 Core	34070	46359	57834	78847	129238	1
20 Core	37677	50835	64151	90297	143373	1
22 Core	41487	56113	70207	-	-	1
25 Core	46535	63156	79915	-	-	1
27 Core	49862	67796	85062	-	-	1

Note : Please contact to HO for Technical Data Sheet.

SHIELDED ARMoured CABLES



RR Kabel makes Flexible / Stranded Bare Copper Conductor PVC / XLPE Insulated, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire / Strip Armour And Outer PVC Sheathed Industrial Instrumentation (Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

SIZE	Size in Sq.mm / Rate Per 100 Meter (in INR)					MOQ (KM)
	0.50	0.75	1.00	1.50	2.50	
2 Core	12258	14217	16071	19288	25863	5
3 Core	14617	17157	19987	23937	33495	5
4 Core	16719	20032	23602	28734	42333	3
5 Core	19179	23393	27858	34052	49726	3
6 Core	21417	26503	31614	40050	-	3
7 Core	22886	28436	33844	43734	65571	3
8 Core	26053	32049	37811	49436	73569	3
9 Core	27859	-	-	-	-	3
10 Core	29925	37626	46064	60909	90503	3
12 Core	33835	42693	52558	68850	106260	3
14 Core	37516	47942	61112	79302	118473	3
16 Core	41933	56586	66019	89235	133876	3
18 Core	47267	57940	73805	99122	148951	3
20 Core	52982	64054	80865	112674	164958	2
22 Core	54163	70071	87604	-	-	2
24 Core	-	-	94106	-	-	2
25 Core	59313	77290	97044	-	-	2
27 Core	62336	81609	107689	-	-	2

Note : Please contact to HO for Technical Data Sheet.

BRAIDED CABLES



RR Kabel makes Flexible / Stranded Bare Copper Conductor, PVC Insulated, Annealed Tinned Copper Braided with Optimum coverage and Outer PVC sheathed Industrial Braided cables, Voltage Grade 300/500V.

Size in Sq.mm / Rate Per 100 Meter (in INR)						
SIZE	0.25	0.50	0.75	1.00	1.50	2.50
2 Core	8359	9626	10450	11827	15081	22075
3 Core	8993	10739	12980	14940	19495	28982
4 Core	10813	13135	16083	18915	24389	37173
5 Core	13543	15343	19253	22546	29803	46234
6 Core	15953	16942	20372	25576	33467	-
7 Core	16840	18392	23486	28228	37770	58756
8 Core	18043	20746	26293	32149	43631	-
9 Core	-	-	-	-	48813	-
10 Core	21558	26353	33409	39808	54230	-
12 Core	23889	28663	38321	46578	63166	98260
14 Core	-	32836	43734	53884	73281	-
16 Core	-	36962	49304	60650	82508	-
18 Core	33619	40790	55264	67845	92168	-

Size in Sq.mm / Rate Per 100 Meter (in INR)				
SIZE	4.0	6.0	10.0	16.0
2 Core	31870	43921	-	-
3 Core	43752	60855	-	-
4 Core	55081	77608	130287	210773

Note : Please contact HO for Technical Data Sheet.

Note : Minimum Order Quantity (MOQ)

Size - upto 0.25 x 8C - 5 KM, upto 0.25 x 8C to 18C and 0.50 to 1.50 x 7C - 3 KM,
0.50 x 8C to 4.0 x 4C - 2 KM, 0.50 x 22C to 1.00 x 27C - 2 KM.

PAIR SHIELDED CABLES



RR Kabel makes Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Pair Shielded) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

Size in Sq.mm / Rate Per 100 Meter (in INR)							
Number of Pair	0.50	0.75	MOQ (KM)	1.00	1.50	2.50	MOQ (KM)
1	7662	9383	10	11625	13390	19270	5
2	12550	15250	5	19459	24176	36230	3
3	16244	20505	3	25852	34097	51528	3
4	18893	26372	3	33187	43374	67314	3
5	23025	32150	3	41143	52569	80516	3
6	26868	37764	3	48990	62292	95721	2
8	34491	48556	3	61541	82386	126019	2
10	42452	58988	3	75745	100846	156219	2
12	50516	70493	3	89911	120026	186359	2
14	-	-	-	-	137682	-	1
16	65611	92179	2	119120	159667	248690	1
20	81481	114923	2	147467	198157	309211	1
24	96661	136724	2	175734	236539	369645	1

RR Kabel makes Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Individual pair and Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Pair Shielded) Cables as per BS EN 50288-7.

Size in Sq.mm / Rate Per 100 Meter (in INR)							
Number of Pair	0.50	0.75	MOQ (KM)	1.00	1.50	2.50	MOQ (KM)
2	16286	18960	5	23225	28781	41058	2
3	21148	26306	5	32611	40223	58172	2
4	27006	32950	3	39619	52362	76143	2
5	31899	39969	3	49681	63556	92922	1
6	37902	48105	2	58247	75445	110577	1
8	50672	62769	2	76978	99159	145850	1
10	62270	77385	1	95082	122783	181024	1
12	73847	91955	1	113170	142220	216135	1
16	97493	118552	1	144851	189427	280388	1
20	120690	146992	1	181541	235505	349033	1
24	143864	175440	1	216835	281560	417654	1
25	-	-	-	225660	-	-	1

Note: The MOQ is given above, please contact HO for Technical Data Sheet.

PAIR SHIELDED ARMoured CABLES



RR Kabel makes Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire/Strip Armour and Outer PVC Sheathed Industrial Instrumentation (Overall Pair Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

Size in Sq.mm / Rate Per 100 Meter (in INR)							
Number of Pair	0.50	0.75	MOQ (KM)	1.00	1.50	2.50	MOQ (KM)
1	12380	14217	10	16225	19288	25863	5
2	19005	22600	5	26448	32301	45095	3
3	22288	26772	3	32032	41697	62194	3
4	26951	33170	3	39715	53832	74707	3
5	30816	39177	3	47792	61246	90233	3
6	35096	45063	3	58292	71479	105952	2
8	45885	56244	3	68503	92784	137028	2
10	50717	66921	3	82778	111836	167820	2
12	59257	78737	3	96875	131235	198364	2
14	-	-	-	-	149793	-	1
16	74786	100471	2	125666	171572	261052	1
20	91090	123263	2	153409	211106	321721	1
24	106476	144895	2	180914	249288	382080	1

RR Kabel makes Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Individual Pair and Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire / Strip Armour and Outer PVC Sheathed Industrial Instrumentation (Individual Pair and Overall Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

Size in Sq.mm / Rate Per 100 Meter (in INR)							
Number of Pair	0.50	0.75	MOQ (KM)	1.00	1.50	2.50	MOQ (KM)
2	22381	26159	5	30053	36053	48038	2
3	27961	32332	5	37641	47210	61166	2
4	33478	40265	3	47521	59487	78373	2
5	40577	49836	3	57855	68405	96636	1
6	47134	54869	2	64497	80143	113730	1
8	56778	69927	2	83418	103356	147629	1
10	68519	84782	1	101499	126344	181263	1
12	80143	99522	1	119443	149177	214712	1
16	103625	129458	1	154514	195846	283294	1
20	126571	158633	1	191611	241285	350019	1
24	149377	187688	1	227080	286564	416543	1
25	-	-	-	235931	-	-	1

Note: The MOQ is given above, please contact HO for Technical Data Sheet.

TERMS & CONDITIONS:

GST : The above prices are exclusive of GST.

Packing : Order should be in Standard packing.

Freight : Value upto Rs. 2,00,000/- on 'TO-PAY' basis & above on 'PAID' basis

Note : This is Revised Price List, hence all previous Price List & Discount will not be considered.

**As per the international practice which is also adopted by BIS, for all cables with ISI mark the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guidelines and are as per market convention, it may vary within the prescribed limit of IS:8130, with related classes and tables.

THE PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.



WORLD OF EXCELLENCE



As a USD 1.25+ billion conglomerate, we are one of the largest, diversified & most prominent brands in the Indian electrical industry, with a noteworthy presence in over 90+ countries across the world. We offer a multi faceted range of quality products through our 10 successfully operating companies, 43 marketing offices and 15 manufacturing facilities.

At RR Global, we continue to innovate to ensure only the finest products reach our customers.



Ram Ratna House, Utopia City, P. B. Marg, Worli, Mumbai - 400 013.

T: +91 - 22 - 2494 9009 / 2492 4144 • **F:** +91 - 22 - 2491 2586 • **E:** mumbai.rrkabel@rrglobal.com

Alembic Business Park (W), Ground Floor, Bhailal Amin Marg, Gorwa, Vadodara - 390 003

T : +91-265-6830 800 • **E:** vadodara.rrkabel@rrglobal.com

R R KABEL LIMITED

Regd. Office : Ram Ratna House, Utopia City, P. B. Marg, Worli, Mumbai - 400 013.

Ahmedabad : 079-4900 0100, **Bengaluru :** 080-4125 0079 / 4090 2221, **Bhubaneswar :** 09776 060 012,
Chennai : 044-2829 2329 / 2429, **Coimbatore :** 09025 168 457, **Ernakulam :** 0484-2378 783,
Guwahati : 07227 004 919, **Indore :** 0731-3515 577, **Jaipur :** 0141-2741 417, **Jalandhar :** 0181-2910 637,
Kolkata : 033-6607 1233, **Lucknow :** 0522-3516 188 / 89, **Madurai :** 0452-4370 340,
New Delhi : 0124-6549 100, **Pune :** 08956 811 100, **Raipur :** 0771-2971 518, **Secunderabad :** 040-27804 098,
Silvassa : 0260-2641 332 / 333, **Surat :** 09376 507 543, **Trichy :** 08939 830 338.

www.rrkabel.com • www.rrglobal.com

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
RoHS = Restriction of Hazardous Substances | **CE** = Conformite Europeenne
ISI = Indian Standard Institution